



PV module - TSM-440NEG9RC.27

Manufacturer	Trina Solar	Commercial data	
Model	TSM-440NEG9RC.27	Availability :	Prod. Since 2021
		Data source :	TSL 2024 01
Pnom STC power (manufacturer)	440 W _p	Technology	Si-mono
Module size (W x L)	1.134 x 1.762 m ²	Rough module area (A _{module})	2.00 m ²
Number of cells	2 x 72	Sensitive area (cells) (A _{cells})	1.81 m ²

Specifications for the model (manufacturer or measurement data)

Reference temperature (T _{Ref})	25 °C	Reference irradiance (G _{Ref})	1000 W/m ²
Open circuit voltage (V _{oc})	52.2 V	Short-circuit current (I _{sc})	10.67 A
Max. power point voltage (V _{mpp})	44.0 V	Max. power point current (I _{mpp})	10.01 A
=> maximum power (P _{mpp})	440.4 W	Isc temperature coefficient (μI _{sc})	4.3 mA/°C

One-diode model parameters

Shunt resistance (R _{shunt})	1000 Ω	Diode saturation current (I _{oRef})	0.012 nA
Series resistance (R _{serie})	0.28 Ω	Voc temp. coefficient (μV _{oc})	-123 mV/°C
Specified P _{max} temper. coeff. (μP _{MaxR})	-0.29 %/°C	Diode quality factor (Gamma)	1.03
		Diode factor temper. coeff. (μGamma)	0.000 1/°C

Reverse Bias Parameters, for use in behaviour of PV arrays under partial shadings or mismatch

Reverse characteristics (dark) (B _{Rev})	3.20 mA/V ²	(quadratic factor (per cell))	
Number of by-pass diodes per module	3	Direct voltage of by-pass diodes	-0.7 V

Model results for standard conditions (STC: T=25 ° C, G=1000 W/m² , AM=1.5)

Max. power point voltage (V _{mpp})	43.4 V	Max. power point current (I _{mpp})	10.20 A
Maximum power (P _{mpp})	441.2 W _p	Power temper. coefficient (μP _{mpp})	-0.29 %/°C
Efficiency(/ Module area) (Eff _{mod})	22.1 %	Fill factor (FF)	0.792
Efficiency(/ Cells area) (Eff _{cells})	24.4 %		

